


Mini Single Side Laser People Counter - Mounting Options

Mount Type

Snap-in

The mounting hole recommended for flush mounting is 30 to 31 mm. The sheet thickness cannot be greater than 3 mm.

Description



Bracket Ball

Suitable for indoor or outdoor use. Perfect for creating a custom solution to your counting requirements. For Example: With doors swinging inwards - use to diagonally point the laser across a doorway to miss the door swing.

Price on application



SHIPPING KIT - MOUNTING BRACKET BALL

Part Name
Shipping kit TOF/Spot mounting bracket ball
housing

Ø 56 mm, height 37 mm

Dimensions

- Ball Bracket ($w \times h \times d$) Material

ASA, black

54 × 36 × 56 mm

- Ball - Bracket Coated stainless steel, black

Outdoor Housing

Has high outdoor weatherability; it retains gloss, colour, and mechanical properties in outdoor exposure. It has good chemical and heat resistance, high gloss, good antistatic properties, and is tough and rigid.

Price on application



SHIPPING KIT - OUTDOOR HOUSING

Part Name	
Shipping kit TOE/Spot outdoor housing	

Dimensions

- Housing (w \times h \times d) 60 \times 64 \times 56 mm

Ø 54 mm, height: 10.8 mm

Cover

- Housing and cover ASA, black

Square Housing Set (Indoors)

Characterized by its high strength, hardness and rigidity to -40 °C this casing is suitable for many mounting situations whilst offering outstanding sensor protection.

Price on application



HOUSING SET

	Part Name
	TOF/Spot Housing Set
_	

Dimensions (w \times h \times d) 45 \times 45 \times 42 mm POM