

People Counter Specifications

	PT Counter Series	Micro Counter Series
Models	Display (PRxD) Wireless (PRxW) USB (PRxU)	Display (MRx11D)
Counting Method	Bi-Directional (PRx_20): separate count for in/out	Non-Directional (MRx11)
Dimensions	116 x 69 x 22 mm (approx)	85 x 53 x 16 mm (approx)
Power Supply	2 x 1.5V AA	1 x 3V Lithium (CR2450)
Battery Life	1 Year (approx)	1 Year (approx)
Maximum Counting Distance	Up to 6 m (unobstructed) Ideal within 4 m	Up to 5 m (unobstructed) Ideal within 3.5 m
Mounting Style	Side & Rear	Rear
Counting Beam	Front	Side
Weather Proof Casing	Optional	-
Mounting Bracket	Rear Mounting Plate Optional Right Angle Bracket	Double Side Adhesive Strip (Included)
Included Software	SensorServer Application for Windows inc. Reports and CSV export (Wireless & USB Models Only)	-
Wireless Frequency	915 MHz 868 MHz optional (Wireless Model Only)	-
Wireless Range to Sensor Network Gateway (SNG)	Up to 20 to 30 metres (Wireless Model Only) <i>Note: SNG requires AC power and RJ45 ethernet</i>	-



Side view of PT Counter (top) compared with Micro Counter



Top view of iPhone 5 (left) compared with PT Counter (middle) and Micro Counter



Flat/rear mount of Micro Counter (top) compared with side mount of PT Counter on door frame



For more information visit www.evolveplus.com.au

EvolvePlus Pty Ltd p: 03 8560 3200 e: sales@evolveplus.com.au

This publication is provided for information and illustrative purposes only, and subject to change without notice.